

MR60-65-75-85 B



Mr60-65-75-85 B.
ESSENTIAL, in terms of reducing cleaning costs

 **FIMAP**[®]
affordable cleaning

MR60-65-75-85 B

Mr scrubbing machines.

They have everything you need with the necessary quality...
... for safety,



SHOCK PROOF

Automatic swing-in of the brush head when accidentally impacted



BREAK AWAY

When accidentally impacted, the squeegee is uncoupled to prevent dangerous situations



FNC (Fimap Noise Canceling)


Thanks to the very low acoustic pressure level cleaning activities can be performed even in highly noise-sensitive environments such as in nursing homes, hospitals and public areas, without disturbing the environment or the people who live in it

... for maximum performance!



FOOD & BEVERAGE

The reduced turning circle allows the Mr to easily turn around in corridors or supermarket aisles



Perfect for effective wall to wall cleaning



Low centre of gravity for optimum stability. Capable of ramp gradients up to 18%

Available equipment:

STANDARD EQUIPMENT	Mr60 B	Mr65-75-85 B
Water and detergent management		
FSS (Fimap Solution Saver) - Manual	•	•
FWF (Fimap Water Flow)	-	•
Eco On/OFF System*	•	-
Fast water filling with drip stop	•	•
Water level indicator	•	•
Scrubbing performance		
Ramp climbing capacity	•	•
Squeegee with polyurethane rubber bars usable on 4 sides	•	•
Variable scrubbing head	-	•
Operating autonomy		
(4) 6V/210 Ah C5 batteries	optional	optional
(2) 12V/130 Ah C5 batteries	optional	optional

STANDARD EQUIPMENT	Mr60 B	Mr65-75-85 B
Comfort		
FNC (FimapNoiseCanceling)	•	•
Fully sanitizable tanks	•	•
Step-through access	•	•
On-board battery charger	optional	optional
Hour meter	•	•
Battery charge level	•	•
Safety		
Anti-skid and non-marking front drive wheel	•	•
Anti-skid and non-marking rear wheels	•	•
Mechanical service and parking brakes	•	•
Flasher	optional	optional
Squeegee with shock-resistant coupling (BREAK AWAY)	•	•
Scrubbing head with impact-elicited swinging in (SHOCK PROOF)	•	•
Dead man's switch	•	•
Horn	•	•

* Eco ON/OFF system: automatically stops water flow when the machine is stationary.



Mr scrubbing machines.

Use operations: The ESSENTIAL

Mr are the first ride-on scrubbing machine on the market with a very simple and intuitive drive:
USER FRIENDLY, as easy as 1, 2, 3!



Mr60 B



Mr65-75-85 B



Working width:
Mr65 B 65 cm
Mr75 B 75 cm
Mr85 B 85 cm

You can start working with just 3 quick and simple operations!

Mr.
Ready for
use without
training



Sit on and Start !



Turn on water and lower decic and squeegee



Go!

ESSENTIAL,
in the cost of cleaning

Mr. A new working method!

Mr: the same size as a traditional walk-behind scrubbing machine
AT THE SAME PRICE!




Mr60 B passes through standard 80 cm doorways and supermarkets





WELLNESS

Mr can clean 1 sq.m of floor for just 1 cent*



Up to 4 hours of NON STOP work,
with:
1 fill of water + 1 full charge!



TIME SAVING FOR CLEANING OPERATIONS

It has been calculated that for the maintenance cleaning of a 3,000 sq.m site working daily 5 days a week and 45 weeks a year (225 washes/year),
THERE IS AN ADDITIONAL TIME SAVING OF 40%
compared to a walk-behind scrubbing machine.

* For further information, contact the Sales Office

at checkouts. Can be transported between floors in a standard lift

LEISURE & HOSPITALITY



LARGE RETAILERS



ESSENTIAL, for every day maintenance operations...

... maintenance has never been so easy and quick.
Easily performed by any operator, even untrained



Empty the tanks...



... and sanitise them!



Clean the squeegee!



The squeegee does not require any tools to
replace or rotate the blades

Park and
Recharge!











An on-board charger option makes battery
re-charging safe and easy (on request)

Mr scrubbing machines are available in the following version:

Professional Line

TECHNICAL DATA		Mr60 B	Mr65 B	Mr75 B	Mr85 B
Squeegee width	mm	780	970	970	1085
Disc brushes Ø	(No.) mm	(1) 610	(2) 340	(2) 390	(2) 430
Brush motor	V/W	(1) 24/450	(2) 24/450	(2) 24/450	(2) 24/450
Brush rpm	rpm	170	170	170	170
Brush pressure	kg	30	30	30	30
Suction motor	V/W	24/310	24/310	24/310	24/310
Traction motor	V/W	24/400	24/400	24/400	24/400
Suction vacuum	mbar	160	160	160	160
Forward speed	km/h	0÷6	0÷6	0÷6	0÷6
Turning diameter	mm	1910	1910	1910	1910
Type of drive	-	aut.	aut.	aut.	aut.
Battery compartment dimensions (L x h x w)	mm	520x340x384	520x340x384	520x340x384	520x340x384
Max gradient at full load	%	fino a 18	fino a 18	fino a 18	fino a 18
Batteries	V/Ah C5	6/210 (4)	6/210 (4)	6/210 (4)	6/210 (4)
Batteries weight	kg	136	136	136	136
Machine weight (without battery)	Kg	223	223	223	223

PROFESSIONAL LINE	 Electromagnetic compatibility Emission standard	 Working width cm	 Number of brushes	 Supply V/ traction	 Solution tank l	 Recovery tank l	 Working capacity up to sq.m/h	 Machine dimensions in mm L x h x w
Mr60 B	EN 6100-6-1, 2, 3, 4	61	1	24/aut.	110	125	3660	1495x1320x680
Mr65 B		65	2				3900	1495x1320x680
Mr75 B		75	2				4500	1495x1320x680
Mr85 B		85	2				5100	1495x1320x680



Saves up to 50% on water and detergent



Reduction of energy consumptions to increase working autonomy



Operate in environments without noise disturbance



It guarantees a uniform solution quantity on the whole working width



24 months extended warranty



Fimap Certified Quality

For any additional information or for a demo please contact your usual Fimap dealer

Dealer's stamp



affordable cleaning

www.fimap.com

Fimap Spa reserves the right, at anytime, to make technical and/or equipment modifications without prior notification. The images are shown as reference only and are not binding as to the actual design and/or equipment - Copyright © Fimap 2010 COD. 301601 - AB - 06-2011

An ISO 9001:2000, ISO 14001:2004,
OHSAS 18001:2007
Organisation certified by Q.C.B. Italy

FIMAP spa - Via Invalidi del Lavoro, 1 - 37050 S. Maria di Zevio - Verona - Italy
Tel. +39 045 6060411 - Fax +39 045 6060417 - E-mail: fimap@fimap.com

